



# WILDPEAK M/T

**WILDPEAK M/T**

**MAXIMUM OFF-ROAD TRACTION BUILT FOR THE TOUGHEST TERRAIN**

Trusted by the pros to take on the harshest conditions, the tough **WILDPEAK M/T** is built to get you there and back whether you're on the pavement, mud, snow or rocks. The M/T features Falken's proprietary three-ply **DURASPEC™** Sidewall Technology developed to sustain the most punishing off-road conditions. **DURASPEC™** also features two high ply turn-ups that provide an additional layer of protection and durability. An aggressive upper sidewall provides additional traction at low air pressures on rugged terrain. The **WILDPEAK M/T** also features exceptional road manners thanks to an optimised variable three-pitch tread pattern and precision manufacturing technology.

**AVAILABLE TYRE SIZES**  
19 SIZES

**AVAILABLE RIM SIZING**  
15" – 20"

**SPEED RATING**  
Q

## PERFORMANCE RATINGS\*



### POPULAR FITMENTS:

- Toyota FJ Cruiser
- Jeep Wrangler
- Nissan Patrol
- Hummer H3
- Land Rover Defender
- Toyota Hilux
- Toyota LandCruiser
- Toyota LandCruiser Prado
- Mitsubishi Triton
- Mazda BT-50
- Holden Rodeo
- Mitsubishi Pajero
- Isuzu Ute D-Max
- Jeep Wrangler
- Nissan Patrol
- Nissan Navara

## TYRE HIGHLIGHTS



**RUGGED AND RIGID TREAD BLOCKS**  
Feature step-down supports on the center blocks to provide tread-pattern rigidity in the contact patch, enhancing stability and handling while preventing stones from becoming trapped in the grooves.



**AGGRESSIVE UPPER SIDEWALL**  
Along with offset shoulder blocks protect the tyre from sharp rocks and provide additional off-road traction at low tyre pressures or in off-camber situations.



**MUD AND ROCK DEFENSE FEATURES**  
Shed mud from the tread grooves to prevent loss of traction, ensuring maximum grip while preventing rocks from puncturing the base of the tread.



**OPTIMISED TREAD PATTERN**  
With three variable pitches positions the tread blocks to provide an exceptionally quiet ride.



### DURASPEC™ THREE PLY SIDEWALL

Is a Falken proprietary technology developed to endure the most punishing off-road conditions. **DURASPEC™** also features two high ply turn-ups that provide an additional layer of protection.

## SIZES AND SPECIFICATIONS

[NEXT PAGE](#)

\*Performance ratings are based on a scale of 1 to 5 with 5 being best. Ratings are in comparison to other Falken Tyres products in the same category.

Product specifications for informational purposes only. Tread design, technical information and tyre construction subject to change without notice and may vary by size.

# WILDPEAK M/T

WILDPEAK M/T

MAXIMUM OFF-ROAD TRACTION BUILT FOR THE TOUGHEST TERRAIN

Wheel Dia. (in)	M-Code	Width	Series	Wheel Dia.	Size Description	LI/SS	Suggested Rim Width (in)	Rim Width Range (in)	Tread Width (mm)	Section Width (mm)	Tread Depth (mm)	Overall Width (mm)	Overall Diameter (mm)	Max Air (psi)	Static Loaded Radius (mm)	Revs per km	Rolling Circ. (mm)	Sidewall Type
15	318941	-	-	15	30X9.50R15LT 104Q WILDPEAK M/T MT01	104Q	7.5	6.5 - 8.5	182	245	15.0	247	751	-	346	443	2255	RBL
	318899	-	-	15	31X10.50R15LT 109Q WILDPEAK M/T MT01	109Q	8.5	7.0 - 9.0	202	266	15.0	268	781	50	359	427	2344	RBL
	318937	-	-	15	33X12.50R15LT 108Q WILDPEAK M/T MT01	108Q	10.0	8.5 - 11.0	240	331	16.4	333	829	35	378	404	2474	RBL
	318939	-	-	15	35X12.50R15LT 113Q WILDPEAK M/T MT01	113Q	10.0	8.5 - 11.0	240	328	16.4	330	876	-	398	383	2610	RBL
16	318905	235	85	16	LT235/85R16 120Q WILDPEAK M/T MT01	120Q	6.5	6.0 - 7.5	178	235	14.4	237	808	80	372	408	2451	RBL
	318959	245	75	16	LT245/75R16 120Q WILDPEAK M/T MT01	120Q	7.0	6.5 - 8.0	198	253	14.5	255	773	80	357	426	2347	RBL
	318907	265	75	16	LT265/75R16 123Q WILDPEAK M/T MT01	123Q	7.5	7.0 - 8.0	214	270	15.0	272	814	80	374	406	2465	RBL
	318945	285	75	16	LT285/75R16 126Q WILDPEAK M/T MT01	126Q	8.0	7.5 - 9.0	230	292	15.5	294	831	80	382	397	2521	RBL
	318947	315	75	16	LT315/75R16 127Q WILDPEAK M/T MT01	127Q	8.5	8.0 - 11.0	254	321	16.5	323	881	-	403	375	2667	RBL
17	318931	265	70	17	LT265/70R17 121Q WILDPEAK M/T MT01	121Q	8.0	7.0 - 8.5	214	269	15.0	271	805	80	373	408	2450	RBL
	318949	285	70	17	LT285/70R17 121Q WILDPEAK M/T MT01	121Q	8.5	7.5 - 9.0	230	290	15.5	292	835	80	385	395	2533	RBL
	318955	295	70	17	LT295/70R17 121Q WILDPEAK M/T MT01	121Q	8.5	7.5 - 10.0	238	298	16.0	300	848	-	391	389	2574	RBL
	318903	315	70	17	LT315/70R17 121Q WILDPEAK M/T MT01	121Q	9.5	8.0 - 11.0	238	325	15.8	327	880	-	404	375	2665	RBL
	318901	-	-	17	35X12.50R17LT 121Q WILDPEAK M/T MT01	121Q	10.0	8.5 - 11.0	240	331	16.4	333	883	-	405	378	2644	RBL
	318935	-	-	17	37X12.50R17LT 124Q WILDPEAK M/T MT01	124Q	10.0	8.5 - 11.0	240	334	16.4	336	932	50	423	362	2766	RBL

OWL: Outlined White-sidewall Letters  
RBL: Raised Black-sidewall Letters

Wheel Dia. (in)	M-Code	Width	Series	Wheel Dia.	Size Description	LI/SS	Suggested Rim Width (in)	Rim Width Range (in)	Tread Width (mm)	Section Width (mm)	Tread Depth (mm)	Overall Width (mm)	Overall Diameter (mm)	Max Air (psi)	Static Loaded Radius (mm)	Revs per km	Rolling Circ. (mm)	Sidewall Type
18	318951	275	70	18	LT275/70R18 125Q WILDPEAK M/T MT01	125Q	8.0	7.0 - 8.5	222	278	15.5	280	848	-	393	388	2580	RBL
	318963	285	65	18	LT285/65R18 125Q WILDPEAK M/T MT01	125Q	8.5	8.0 - 10.0	230	295	14.9	297	833	-	385	396	2525	RBL
20	318973	305	55	20	LT305/55R20 121Q WILDPEAK M/T MT01	121Q	9.5	8.5 - 11.0	256	314	15.4	316	847	-	393	388	2576	RBL
	318933	-	-	20	35X12.50R20LT 121Q WILDPEAK M/T MT01	121Q	10.0	8.5 - 11.0	240	321	16.4	323	883	-	411	375	2665	RBL

OWL: Outlined White-sidewall Letters  
RBL: Raised Black-sidewall Letters