



H08

The **H08** is a deep-tread, highway rib, commercial tyre from Toyo Tires.

The H08 is designed for vans and utilities and uses Toyo's advanced technologies to provide high levels of wet traction, long tread life, resistance to shoulder wear and superior ride comfort.

FEATURES

High-grip, wear resistant long-link carbon black tread compound

Deep tread depth

Flat crown radius and square tread shoulders

Rigid shoulder block design

New casing construction

BENEFITS

High levels of wear resistance and wet road grip

Long tread life

Improved wet and dry handling and resistance to irregular wear

High resistance to irregular and accelerated wear of the tread shoulders

Improved ride comfort and casing durability

TYRE SIZE & SERVICE DESCRIPTION	TREAD DEPTH (mm)	INFLATED DIM.		LOADED DIMENSION			TEST RIM (INCH)	REVS PER KM.	APPROVED RIM WIDTH CODES(INCH)
		O.D. (mm)	O.W. (mm)	STATIC RADIUS	STATIC WIDTH	DYNAMIC RADIUS			
175/65R14C 90/88T	10.2	584	179	267	195	283	5.0	562	5.0 - 5.5
175R14 99/98S	10.7	634	180	286	196	308	5.0	518	5.0 - 6.0
185R14 102/100S	10.7	650	193	293	210	316	5.5	504	5.0 - 6.0
195R14 106/104S	10.7	666	201	299	219	323	5.5	493	5.0 - 6.0
205/65R15 102/100T	10.2	644	209	293	228	313	6.0	508	5.5 - 6.5
195/70R15 104/102S	10.2	652	202	296	220	316	6.0	503	5.0 - 6.0

TYRE SIZE & SERVICE DESCRIPTION	TREAD DEPTH (mm)	INFLATED DIM.		LOADED DIMENSION			TEST RIM (INCH)	REVS PER KM.	APPROVED RIM WIDTH CODES(INCH)
		O.D. (mm)	O.W. (mm)	STATIC RADIUS	STATIC WIDTH	DYNAMIC RADIUS			
205/70R15C 106/104S	10.2	667	203	260	221	324	6.0	491	5.5 - 6.5
215/70R15C 109/107S	10.2	680	219	265	239	330	6.5	482	5.5 - 7.0
225/70R15 112/110S	10.7	695	228	313	249	337	6.5	472	6.0 - 7.0
225/75R15 110/108Q	11.2	719	227	280	247	349	6.0	456	6.0 - 7.0
195R15C 106/104S	10.8	690	199	311	217	335	5.5	475	5.0 - 6.0
215/60R16C 103/101T	10.2	667	218	260	238	324	6.5	491	6.0 - 7.0
195/65R16C 104/102R	10.2	661	199	258	217	321	6.0	496	5.5 - 6.0
205/65R16C 107/105T	10.2	671	209	262	228	326	6.0	488	5.5 - 6.5
215/65R16 106/104T	10.2	688	219	268	239	334	6.5	477	6.0 - 7.0
225/65R16 112/110R	10.2	700	228	273	249	340	6.5	468	6.0 - 7.0
235/65R16C 121/119R	10.2	710	244	279	266	345	7.0	461	6.5 - 7.5
215/70R16C 108/106T	10.3	709	219	321	239	344	6.5	463	5.5 - 7.0
185/75R16C 104/102S	10.7	684	185	311	202	332	5.0	480	5.0 - 6.0
195/75R16C 107/105S	10.7	696	197	316	214	338	5.5	472	5.0 - 6.0
205/75R16 113/111Q	11.2	714	204	332	224	347	5.5	459	5.5 - 6.5
215/75R16 116/114R	11.2	728	215	339	235	354	6.0	450	5.5 - 7.0
225/75R16 118/116R	11.2	743	224	334	244	361	6.0	441	6.0 - 7.0